

EXPERT/ FAMILY The Best Choice for Sign Makers

Expert II 24
Expert II 52
Expert II 24 LX
Expert II 52 LX

The Expert Family provides sign makers with optimum speed, superior quality, solid reliability, unmatched value at an affordable price and an eye-catching color combination.



EXPERT/

- 24 in. / 52 in.
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)
- · 3 m tracking



- 24 in. / 52 in.
- Up to 350 gram of cutting force
- Up to 705 mm / 635 mm (27.8 in. / 25 in.) per second cutting speed (at 45 degree direction)
- · 3 m tracking
- Advanced contour cutting system AAS II

Advanced AAS II Contour Cutting System
Advanced Automatic-Aligning System (AAS
II) guarantee precise contour cutting by
detecting the registration marks on digitally
produced images. (Available for Expert II LX

models)



Guaranteed 3 meter tracking – grid drum (patented)

It comes with a stable drum that can guarantee 3 meter tracking to ensure quality outputs and saves you from wasted material and cost.



Handy grooved cut-off tool

This handy and innovative design allows you to cut off a finished job in a straight line easily reducing the possibility of wasting usable material.



VCM (Patented)

VCM (Voice Coil Motor) ensure cutting quality. As a result, Expert II can provide sophisticated cutting quality steadily and consistently.



Windows Drivers

Expert II includes a "one click" Windows driver that allows sign makers to edit signs from CorelDraw and Adobe Illustrator output directly to Expert II.



User-friendly interface

It comes with the special VLCD software, providing a simple and intuitive workflow for users of all levels.



Rhinestone Application

Expert II handles rhinestone stencil cutting with ease, people are amazed with its great versatility.



Dual-port connectivity

GCC Expert II supports dual-port connectivity with USB and serial ports.





Signs Stickers Advertisement

Advertisement		Stickers		rextile	
Model Number		EX II-24	EX II-24LX	EX II-52	EX II-52LX
Operational Method		Roller -Type			
Max. Cutting Width		600 mm (23.6 in.)		1320 mm (51.96 in.)	
Max. Cutting Length		50m (164 ft)			
Max. Media Loading Width		719 mm (28.3 in.)		1470 mm (57.87 in.)	
Min. Media Loading Width		50 mm (1.97 in.)			
Number of Pinch Rollers		3			
Acceptable Material Thickness		0.8 mm (0.03 in.)			
Motor Drive		Stepper			
Cutting Force		350 g			
Max. Cutting Speed		Up to 705 mm / sec (27.8 ips) (at 45 degree direction)		Up to 635 mm / sec (25 ips) (at 45 degree direction)	
Acceleration		0.7 G			
Offset		0 ~ 1.0 mm (with an increase of 0.025 mm)			
Mechanical Resolution		0.012 mm (0.00047 in.)			
Software Resolution		0.025 mm (0.00098 in.)			
Distance Accuracy		± 0.254 mm or ± 0.1% of move, whichever is greater			
Repeatability		±0.1mm			
Automatic-Aligning System (AAS II)		Available on Expert II LX models			
Memory Buffer		32MB / 16MB (when using AAS)			
Interfaces		USB 2.0 (Full speed) & Serial (RS-232C)			
Type of Command		HP-GL, HP-GL / 2			
Control Panel		10 Control Keys and 6 LED			
Diameter of Blade		2.5 mm			
Dimension	(WxDxH) mm	800*2	255 * 233	1633 * 10	069 * 650
	(WxDxH) in.	34.6*	10 * 9.1	64.2 * 42 * 25	.5 (stand included)
Net Weight		11 kg	(24.3 lb)	41 kg (90.2 lb) (stand included)	
Stand		Opti	onal	Standard	
Power Supply		100-240 VAC, 50 / 60 Hz (auto switching)			
Power Consumption		Max. 65 W			
Environment Temperature		15° C ~ 30° C / 60° F ~ 86° F (operating)			
Environment Humidity		25 % ~ 75 % relative humidity (operating)			

- * Compatible with Windows 7 and above & MAC OS X 10.6 and above. (*Purchasing serial number for "Sure Cuts A Lot" software to work with Mac OS.)
- # The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.
- GCC certified material in tracking is Avery MPI 3000.
- * GCC reserves the right to change the specifications without prior notice.
- * The above listed specification values are effective only when operated with media certified by GCC.





GCC China

No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax: 86-512-5726-1518 GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367 GCC America, Inc 20550 Carrey Road, Walnut, CA 91789, USA

GCC Headquarters 4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax: 886-2-2694-6875

US & Canada Only Toll Free: 1-888-284-5211

www.GCCworld.com

1-909-718-0248 Fax: 1-909-718-0251