



StellarMark I-Series Specifications


Model		I-Series			
Model No.		IFIIS 20JFL	IFIIS 30JFL	IFIIS 50JFL	IFIIS 60JFL
Laser Type	Wavelength	1064 nm			
	Type	Yb-doped, MOPA			
	Output Power	20W	30W	50W	60W
	Beam Mode	TEM00			
	Beam Quality (M ²)	<1.5	<1.5	<1.5	<1.8
	Frequency	1-600 kHz	1-1000 kHz	1-600 kHz	1-400 kHz
	Waveform	Single	Single	Single	Single
	Cooling	Air-cooled			
Max. Linear Marking Speed		3,000 mm/s			
Max. Marking Speed		10,000 mm/s			
Electrical Requirement	Power Supply	100-240V, 50/60 Hz Max 15 Amp			
	Power Consumption	Max. 1650W			
Dimensions	Laser head	L497 x W168 x H152 mm			
	Control unit	L470 x W360 x H241 mm			
Laser Head Weight		9 Kg			
Control Unit Weight		25 Kg			
Operating System		Microsoft Windows 2000 / XP / Vista(32/64 Bit) / 7(32/64 Bit) / 8(32/64 Bit) (Desktop or Laptop PCs)			
Environment	Temperature	15° C ~ 35° C			
	Humidity	10 ~ 80%, Non condensing			
Safety		Class 4 (EN60825-1 Class 1 available with safety shield and LFC) 2006/42/EC Machinery Directive 2014/35/EU Low Voltage Directive 2014/30/EU Electromagnetic Compatibility Directive			

Scan Lens Specifications

Specifications	StellarMark IFIIS 20/30/50/60JFL Scan Lens			
Model No.	70	110	180	300
Working Area	70 x 70 mm	110 x 110 mm	180 x 180 mm	300 x 300 mm
Spot Size*	27 µm	44 µm	71 µm	114 µm
Working Distance	142 ±1 mm	220 ±2 mm	350 ±2 mm	553 ±3 mm
Repeatability**	0.03 mm	0.03 mm	0.04 mm	0.06 mm

Above specifications are subject to change without further notices. See dealer or visit <http://www.GCCworld.com> for more details.
 All above spot size will be material dependent.
 *According to theoretical calculation
 **The test is 8-hour continuous firing with power level at 30% using a 60JFL
 Δ Specifications are subject to change without prior notice


Optional Items



Authorized Dealer



www.GCCworld.com



- ▶ Field proven U.S. scan head and UK fiber laser components
- ▶ Achieve 0.1mm character height with perfect TEM00 beam mode
- ▶ Multiple waveform are available for sophisticated marking and micro-machining applications
- ▶ G-Mark Library (optional) software features customized programming, mark on fly and tiling marking
- ▶ Ideal solution for ABS, PC, PET, wafer, rubber and metal marking



GCC Headquarters 4F-1, No.236, Fude 2nd Rd., Xzhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax: 886-2-2694-6875
 GCC China No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax: 86-512-5726-1518
 GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367
 GCC America, Inc 20550 Carrey Road, Walnut, CA 91789, USA 1-909-718-0248 Fax: 1-909-718-0251
 US & Canada Only Toll Free: 1-888-284-5211

StellarMark I-Series

Design in top-notch U.S. scan head and U.K. fiber laser source, StellarMark I series provides industrial users superior and reliable output quality under long-term operation. From automotive parts and tools to electronic switch and wafer, StellarMark I series provides comprehensive solution for diverse requirements.

Superior Output Performance >>>>>

Benefiting from the state-of-the-art design, StellarMark I-Series stands out from the competition by increasing productivity and providing superior output quality. The TEM00 beam mode brings in high precision marking results and stable laser output maintain consistent marking quality. Different M2 values are available with the different models under the IF-series catering to the different requirements for different applications.



IFIS 20JFL / 30JFL / 50JFL / 60JFL


Application



Depth Marking




Color Marking



Glass Marking



Keypad Marking



Wafer Marking



IC Marking


Consistent Power Stability

GCC LaserPro

Others

Superior Text Function

- Automatic Serial Marking
- Barcode Marking
- Wobble Marking
- Jump Cross Marking
- Font Variation
- Logo and Image Marking
- Arc Marking



Jump Cross Marking



Wobble Marking



Arc Marking



Barcode Marking



Automatic Serial Marking

Key Switch

This safety feature enables operators to keep the laser locked to avoid unauthorized use.



Emergency Stop

The machine can be entirely shut down by pressing the "Emergency Stop" button from controller when any emergency occurs.




Pyramid Focus Tool

The innovative and patented pyramid focus tool is an accessory unit for providing the best working distance on StellarMark IFIS series.




Preview Mode

Variable speed, red dot pointer "preview" mode allows for accurate and easy marking positioning on the marked part.



Full Path



Outline

Mark On Fly (Optional)

An optional software function that features marking of moving objects on a conveyor.



G-Mark Library (Optional)

This programmable software can be used to customize functions by using VB scripts. All commands are received real time from a master PC and position offsets, rotating angle, and sequential marking can be set up. With G-Mark Library, the workflow of marking process can be optimized and simplified at the production line.

